

Flush Sliding Bolt
2201



Flush Sliding Bolt
2211



Flush Sliding Bolt
2221



Flush Sliding Bolt
2231



Short Flush Sliding Bolts

These bolts are for situations where there is restricted height for the concealed mounting versions and therefore require visible fixings.

Offsets and strike options are as shown on the Flush Sliding Bolts page.

A – 10.5mm

B – 5.5mm

Flush Sliding Bolt – 10mm Throw

55mm x 65mm: 2201

Flush Sliding Bolt – 15mm Throw

55mm x 80mm: 2211

Flush Sliding Bolt – 20mm Throw

55mm x 100mm: 2221

Flush Sliding Bolt – 40mm Throw

55mm x 140mm: 2231

To order bolt specify: (examples)

Code Number	Offset Dimension	Finish
2201	5.5mm	SCPV
2211	10.5mm	PBZ

To order strike specify: (examples)


Code Number	Finish
2092	SCPV
2091	PBZ

Please contact chant™ if you have a requirement for custom variations of these Flush Sliding Bolts.


Key Insert Lock 2899
Insert position



Lock position



Retract key, insert remains



Key Insert Lock

Our Key Insert Lock is used to lock the bolts on our Flush Sliding Bolts and Square Bolts. The 'insert' part of the lock which is attached to the key, is inserted into the bolt to be locked, the key rotated 90° and then withdrawn. The bolt is then prevented from operating. To unlock, insert the key, rotate and remove the insert. This is a practical alternative to wafer locks that can be easily forced and cannot be master-keyed; or much larger locks that may be master-keyed, but interfere with the door structure.

These are included in the pricing of our Flush Sliding Bolts and Square Bolts. They are also priced individually as replacements.

Keys are only available in a Polished Chrome finish. Insert is available in Polished Chrome, Polished Brass Uncoated or Weathered Brass.